

COLORado™ 1-Quad IP



COLORado™ 1-Quad IP loads seven quad-colored LEDs into a compact, robust IP66-rated housing, perfect for any lighting rig, indoors or out. The white in the quad-colored emitters is conducive to a truer white spectrum and boosts the overall color range to include more subtle pastels. A versatile split-yoke bracket allows floor or truss mounting. COLORado™ 1-Quad IP also includes a gel frame holder.

FEATURES

- Built-in auto and custom programs recalled via DMX and Master/Slave
- RGBW color mixing via DMX or manually
- Color temperature presets, from 3200 to 10000 K
- Individual control of outer pixel ring and center pixel
- 5 distinct dimming curves
- LED display with password protection
- M12 GORE® valve for assured internal equalization
- Simple and complex DMX channel profiles for programming versatility
- Double-bracket yoke doubles as floor stand

SPECIFICATIONS

- DMX Channels: 3, 4, 5, 6, 8, 10, 15 or 23
- Data Connectors: 5-pin XLR
- Light Source: 7 LEDs (quad-color RGBW) 10 W, (2.8 A), 50,000 hours life expectancy
- Accessory Holder/
Gel Frame Size: 7.5 in (191 mm)
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Stand Alone Color
Mixing: Yes
- Color Temperature
Presets: Yes
- Installed Optics: 8°
- Beam Angle: 11.5°
- Field Angle: 25°
- Dimming Modes: 5
- Illuminance: 1,520 lux @ 5 m
- Color Temperature
(range): 2800 to 10000 K
- IP Rating: IP66 outdoor/wet, with pressure equalizing M12 Gore® valve
- Cable Length
(signal extension): 16.4 ft (5 m)
- Cable Length
(power extension): 16.4 ft (5 m)
- Power Connection: Edison plug to proprietary IP66 input power cord (65 in/1,651 mm)
- Power Input: Proprietary IP66
- Power Output: Proprietary IP66
- Power Linking: 11 units @ 120 V; 19 units @ 208 V; 21 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 81 W, 1.15 A @ 120 V, 60 Hz
- Power and Current: 80 W, 0.69 A @ 208 V, 60 Hz
- Power and Current: 79 W, 0.63 A @ 230 V, 50 Hz
- Weight: 11.5 lb (5.22 kg)
- Dimensions: 7.5 x 9.4 x 11.7 in (191 x 239 x 299 mm)
- Approvals: CE, MET