

# STRIKE™ 4



Meet the STRIKE™ 4, CHAUVET® Professional's answer to your multi-format LED warm-white wash needs! STRIKE™ 4 features four independently focusable 100W chip-on-board LEDs that provide incredible output and coverage for a wide gamut of production genres. STRIKE™ 4 features smooth 16-bit dimming control for those incandescent-style fades, a series of automated strobe effects for using the STRIKE™ 4 as an audience blinder, individual manual pan control of each LED pod and adjustable PWM for using the STRIKE™ 4 in film and studio locations. STRIKE™ 4 comes standard with basic and advanced control personalities for flexibility in programming, and an easy-to-read OLED display for quick onboard adjustments.

## FEATURES

- 16-bit dimming control for smooth, perfect fades
- Individual pan of each head to allow for directional adjustment of light output
- Simple and complex DMX channel profiles for programming flexibility
- Easy to use OLED display
- Automated strobing programs for easy programming
- Adjustable Pulse Width Modulation (PWM) control to eliminate flicker on camera

## PRELIMINARY SPECIFICATIONS

- DMX Channels: 1, 3, 4 or 9
- Data Connectors: 5-pin XLR
- Light Source: 4 LEDs (WW) 100 W, (2.3 A ), 3096 K, 50,000 hours life expectancy
- Pan: ±24°
- Built-in Automated Programs: Yes
- Dimmer: Electronic
- Strobe Rate: 0 to 30 Hz
- Beam Angle: 49°
- Field Angle: 79°
- Dimming Modes: 4
- Illuminance (total): 640 lux @ 5 m
- Illuminance (per cell): 165 lux @ 5 m
- Color Temperature (at full): 3096 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison (Local) plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 5 units @ 120 V; 9 units @ 208 V; 10 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 301 W, 2.49 A @ 120 V, 60 Hz
- Power and Current: 287 W, 1.43 A @ 208 V, 60 Hz
- Power and Current: 286 W, 1.29 A @ 230 V, 50 Hz
- Weight: 19 lb (8.7 kg)
- Dimensions: 14.2 x 6.4 x 14.2 in (362 x 163 x 362 mm)
- Approvals: CE