

COLORado™ 1-Tri IP



COLORado™ 1-Tri IP is an IP66-rated LED wash with 14 intense, calibrated tri-color LEDs. This outdoor-rated workhorse is an ideal front light as high efficiency optics and tri-colored LEDs eliminate multicolored shadows while five dimming curves ensure compatibility with older non-LED rig. Optional (20 and 60 x 1-degree) color blending filters further enhance this unit's outstanding performance. COLORado™ 1-Tri IP also includes a built-in gel frame holder.

FEATURES

- Built-in auto and custom programs recalled via DMX and Master/Slave
- RGB color mixing via DMX or manually
- Color temperature presets, from 2800 to 10000 K
- 5-pin DMX input/output connections
- 16-bit dimming of master dimmer and individual colors
- 5 distinct dimming curves
- LED display with password protection
- IP66 rated for outdoor water and dust protection
- M12 GORE® valve for assured internal equalization
- Simple and complex DMX channel profiles for programming versatility
- Double-bracket yoke doubles as floor stand
- Tri-color RGB LEDs

SPECIFICATIONS

- DMX Channels: 3, 4, 5, 9 or 13
- Data Connectors: 5-pin XLR
- Light Source: 14 LEDs (tri-color RGB) 3 W, (700 mA), 50,000 hours life expectancy
- Accessory Holder/
Gel Frame Size: 7.5 in (191 mm)
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color
Mixing: Yes
- Color Temperature
Presets: Yes
- Installed Optics: 16°
- Beam Angle: 15°
- Field Angle: 28°
- Dimming Modes: 8
- Illuminance: 806 lux @ 5 m
- Color Temperature
(range): 2800 to 10000 K
- IP Rating: IP66, outdoor/wet, with pressure equalizing M12 GORE® valve
- Cable Length: 5 ft (1.5 m)
- Cable Length
(signal extension): 16.4 ft (5 m)
- Cable Length
(power extension): 16.4 ft (5 m)
- Power Connection: Edison plug to proprietary IP66 input power cord (65 in/1,651 mm)
- Power Input: Proprietary IP66
- Power Output: Proprietary IP66
- Power Linking: 14 units @ 120 V; 24 units @ 208 V; 26 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 87 W, 0.73 A @ 120 V, 60 Hz
- Power and Current: 91 W, 0.44 A @ 208 V, 60 Hz
- Power and Current: 93 W, 0.40 A @ 230 V, 50 Hz
- Weight: 9.6 lb (4.4 kg)
- Dimensions: 8 x 9.7 x 9.5 in (202 x 246 x 242 mm)
- Approvals: CE, MET