


AT A GLANCE:

RGBW Color Mixing



Key Features:

- 7, 10 W quad color LEDs deliver a full range of color mixing with truer whites
- Even and precise 11deg beam angle provides plenty of punch through the brightest of stage washes
- Silent, fan-free operation allows for use in noise sensitive environments
- Direct 3 & 5-pin DMX in/out and powerCON in/out make connections a breeze.
- Flicker free performance, makes the fixture safe for use on camera
- Built-in color temperature presets provide predictable color every time.

About this light:

COLOrado™ 1 Quad Tour loads seven quad-colored LEDs into a compact and robust housing. The incorporation of white in the quad-colored LEDs provides a truer white spectrum and an overall boost in color output for more subtle pastels. A split yoke bracket allows floor or truss mounting. Neutrik powerCON and direct 3 and 5-pin DMX connections make setup fast and easy.



DETAILED SPECIFICATIONS:

FEATURES

- 3, 4, 5, 6 or 11 Quad Color LED wash light
- Operating modes
 - 3-channel: RGB control
 - 3-channel: HSV control
 - 4-channel: RGB, dimmer
 - 4-channel: RGBW
 - 5-channel: RGBW, dimmer
 - 6-channel: RGBW, dimmer, strobe
 - 11-channel: RGBW, ID addressing, dimmer, strobe, macro, auto/custom, dimmer curve, auto speed
- RGBW color mixing with or without DMX control
- Color temperature presets (3,200 ~ 10,000 K)
- Built-in automated programs via master/slave, DMX
- Recall custom programs via master/slave or DMX
- Five distinct dimming curves
- RGBW Quad Color LEDs
- Electronic dimmer
- Color macros with speed adjustment included
- Electronic power supply
- Neutrik powerCon connectors
- 3-pin and 5-pin DMX input and output connectors
- Additional power output: max 12 units @ 120 V
- LED display with password protection
- Gel frame holder (4 mm max thickness)
- Double-bracket yoke doubles as floor stand
- Color Calibration

SPECIFICATIONS

- DMX connectors: 3-pin and 5-pin
- Source: 7 (10 W) quad-color LEDs, 50,000 hours
- Configuration: 7 RGBW (700mA per die)
- Installed Optic(s): 8°
- Beam Angle: 11.5°
- Field Angle: 20°
- Lux: 1,650 @ 5 m
- AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
- Power Consumption 120 V, 60 Hz: 66 W, 0.6 A (operating)
- Power Consumption 230 V, 50 Hz: 65 W, 0.3 A (operating)
- Power linking: 10 units @ 120 V / 20 units @ 230 V
- Dimensions: 8.7 x 9.3 x 13.1 in (222 x 235 x 335 mm)
- Weight: 11.5 lbs (5.2 kg)
- Power Connection: Neutrik powerCON power input and output connector
- Control Connection: 3-pin and 5-pin DMX input and output connectors
- Certification: CE, ETLc
- Environment: IP20, dry location