

# COLORdash™ Batten-Quad 6



COLORdash™ Batten-Quad 6 is a linear wash fixture with six quad-colored RGBA LEDs outputting any variation of white, as well as richly saturated colors, thanks to the inclusion of amber LEDs. It maintains an even pixel pitch when used in multiples, either stacked in an array using the optional CBB6 bracket or lined up end-to-end. Setup is greatly eased by a hanging bracket, floor trunnions, 3- and 5-pin DMX connectors, locking IEC power input, and power linking.

## FEATURES

- Metal construction for added durability
- Individual pixel control
- Silent flicker-free operation
- Simple and complex DMX channel profiles for programming versatility
- Mount multiple units in stack or end-to-end to maintain pixel pitch

## SPECIFICATIONS

- DMX Channels: 4, 6, 10, 24 or 28
- Data Connectors: 3- and 5-pin XLR
- Light Source: 6 LEDs (quad-color RGBA) 7 W, (500 mA), 50,000 hours life expectancy
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Stand Alone Color Mixing: Yes
- Color Temperature Presets: Yes
- Installed Optics: 20°
- Beam Angle: 17°
- Field Angle: 33°
- Dimming Modes: 4
- Illuminance: 390.7 lux @ 5 m
- Color Temperature (range): 2,800 to 10,000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Control Connection: 3- and 5-pin XLR DMX input and output connectors
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 17 units @ 120 V; 30 units @ 208 V; 33 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 90 W, 0.76 A @ 120 V, 60 Hz
- Power and Current: 94 W, 0.45 A @ 208 V, 50 Hz
- Power and Current: 96 W, 0.41 A @ 230 V, 50 Hz
- Weight: 5 lb (2.3 kg)
- Dimensions: 22 x 2.6 x 6.5 in (560 x 65 x 164 mm)
- Approvals: CE, MET