

COLORdash™ Par-Quad 18



COLORdash™ Par-Quad 18 is powered by 18 quad-colored RGBA LEDs in a compact and durable housing. Amber LEDs help produce any variation of white and stunning saturated colors for an expansive palette devoid of multi-colored shadows. A split-yoke bracket eliminates the need for floor stands. Power linking with powerCON in and out and 3- and 5-pin DMX connectors simplify connections and setup. COLORdash™ Par-Quad 18 also includes a built-in gel frame holder.

FEATURES

- 4, 6 or 10 DMX channels
- Silent flicker free operation
- Lightweight, easy to install
- Metal construction for added durability

SPECIFICATIONS

- DMX Channels: 4, 6 or 10
- Data Connectors: 3- and 5-pin XLR
- Light Source: 18 LEDs (quad-color RGBA) 7 W, (500 mA), 50,000 hours life expectancy
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Stand Alone Color Mixing: Yes
- Color Temperature Presets: Yes
- Installed Optics: 20°
- Beam Angle: 18°
- Field Angle: 32.5°
- Dimming Modes: 4
- Illuminance: 1,210 lux @ 5 m
- Color Temperature (range): 2,800 to 10,000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 14 units @ 120 V; 24 units @ 208 V; 26 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 113 W, 0.95 A @ 120 V, 60 Hz
- Power and Current: 115 W, 0.56 A @ 208 V, 50 Hz
- Power and Current: 117 W, 0.51 A @ 230 V, 50 Hz
- Weight: 10.2 lb (4.6 kg)
- Dimensions: 12.7 x 11.7 x 4.1 in (323 x 298 x 106 mm)
- Approvals: CE, MET