

COLORdash™ Batten-Quad 12



COLORdash™ Batten-Quad 12 is a linear wash fixture with 12 individually controlled quad-colored RGBA LEDs that produce any variation of white, as well as richly saturated colors, due to the inclusion of amber LEDs. It maintains an even pixel pitch when used in multiples, either stacked in an array using the optional CBB6 bracket or lined up end-to-end. Setup is easy when using the hanging bracket, floor trunnions, 3- and 5-pin DMX connectors, and power linking.

FEATURES

- Built-in auto and custom programs recalled via DMX or Master/Slave
- Metal construction for added durability
- Individual pixel control
- Silent flicker-free operation
- Mount multiple units in stack or end-to-end to maintain pixel pitch

SPECIFICATIONS

- DMX Channels: 4, 6, 10, 48 or 52
- Data Connectors: 3- and 5-pin XLR
- Light Source: 12 LEDs (quad-color RGBA) 7 W, (500 mA), 50,000 hours life expectancy
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Stand Alone Color Mixing: Yes
- Color Temperature Presets: Yes
- Installed Optics: 20°
- Beam Angle: 22°
- Field Angle: 31°
- Dimming Modes: 4
- Illuminance: 539 lux @ 5 m
- Color Temperature (range): 2,800 to 10,000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 9 units @ 120 V; 16 units @ 208 V; 17 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 175 W, 1.45 A @ 120 V, 60 Hz
- Power and Current: 168 W, 0.81 A @ 208 V, 60 Hz
- Power and Current: 175 W, 0.76 A @ 230 V, 50 Hz
- Weight: 10.6 lb (4.8 kg)
- Dimensions: 41 x 3.2 x 6.5 in (1041 x 82 x 164 mm)
- Approvals: CE, MET