

# COLORdash™ Par-Quad 7



Powered by seven quad-color RGBA LEDs, the ultra-compact COLORdash™ Par-Quad 7 fits in places where other fixtures cannot. The seven LEDs project deeply saturated output and any variation of white, without multi-color shadows. A split-yoke bracket eliminates the need for floor stands. Power linking with Neutrik® powerCON® in and out connectors, and 3- and 5-pin DMX connectors ease connections and setup. COLORdash™ Par-Quad 7 also includes a built-in gel frame holder.

## FEATURES

- 4, 6 or 10 DMX channels
- Silent flicker-free operation
- Lightweight, easy to install
- Metal construction for added durability

## SPECIFICATIONS

- DMX Channels: 4, 6 or 10
- Data Connectors: 3- and 5-pin XLR
- Light Source: 7 LEDs (quad-color RGBA) 7 W, (500 mA), 50,000 hours life expectancy
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Installed Optics: 20°
- Beam Angle: 18°
- Field Angle: 32.5°
- Dimming Modes: 4
- Illuminance: 434 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 21 units @ 120 V; 36 units @ 208 V; 39 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 73 W, 0.60 A @ 120 V, 60 Hz
- Power and Current: 73 W, 0.36 A @ 208 V, 50 Hz
- Power and Current: 74 W, 0.35 A @ 230 V, 50 Hz
- Weight: 5.4 lb (2.5 kg)
- Dimensions: 9.9 x 9 x 3.9 in (252 x 228 x 100 mm)
- Approvals: CE, MET