

Ovation™ F-95WW



Ovation™ F-95WW features a compact and lightweight design that delivers a beautiful soft flat field with high-quality glass optics. Ovation™ F-95WW is built to work on its own in a variety of stage and TV applications, and jointly with the larger Ovation™ F-165WW. Its massive zoom range of 21° to 83° and beautifully soft, warm white wash make it a versatile replacement for aging six-inch fresnels. A virtually quiet operation and smooth dimming control make it a perfect choice for any theatrical and/or studio application.

FEATURES

- 16-bit dimming resolution for smooth fades
- Flat, even field of light
- Virtually silent operation for use in any situation
- Simple and complex DMX channel profiles for programming versatility
- Manually controlled variable zoom angle between 21° to 83°

SPECIFICATIONS

- DMX Channels: 1, 2 or 3
- Data Connectors: 3- and 5-pin XLR
- Light Source: 9 LEDs (WW) 10 W, (2.8 A), 100,000 hours life expectancy
- Accessory Holder/
Gel Frame Size: 6.25 in/159 mm
- Dimmer: Electronic
- Focus: Manual
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 11° to 60°
- Field Angle: 21° to 83°
- Zoom Angle: 21° to 83°
- Dimming Modes: 9
- Lumens (21°): 1,681
- Lumens (83°): 3,741
- Illuminance (21°): 1,430 lux @ 5 m
- Illuminance (83°): 133 lux @ 5 m
- Color Temperature (at full): 3199 K
- Max. Noise Level (studio): 41 dB @ 12 in (305 mm)
- Max. Noise Level (power): 43 dB @ 12 in (305 mm)
- Max. Noise Level (live): 42 dB @ 12 in (305 mm)
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 15 units @ 120 V; 25 units @ 208 V; 28 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 108 W, 0.89 A @ 120 V, 60 Hz
- Power and Current: 110 W, 0.53 A @ 208 V, 60 Hz
- Power and Current: 110 W, 0.48 A @ 230 V, 50 Hz
- Weight: 13.4 lb (6.1 kg)
- Dimensions: 12.8 x 11 x 15.2 in (325 x 279 x 389 mm)
- Approvals: CE, MET