

# COLORado™ 2-Quad Zoom Tour



Powerful, reliable, road-ready - the COLORado™ 2-Quad Zoom Tour is a PAR-style powerhouse featuring 14 quad-color RGBW 15-watt LEDs, a versatile digitally or manually controlled zoom range, and color temperature presets from 3200 K to 10000 K for use across markets. COLORado™ 2-Quad Zoom Tour's versatile zoom range and five dimming curves allows designers to have creative freedom to use the fixture as a beam, wash, or both in the same rig. Secure Neutrik® powerCON® as well as 3-pin and 5-pin DMX input/output connections make it standard, and its tough construction make it a perfect addition to your international tours.

## FEATURES

- RGBW color mixing via DMX or manually
- Zoom control via DMX or manually
- Color temperature presets 3200 to 10000 K
- Built-in auto and custom programs recalled via DMX and Master/Slave
- 16-bit dimming of individual colors as well as master dimmer
- Selectable, smooth dimming curves for programming versatility
- Color macros with included speed adjustment
- Double-bracketed yoke doubles as a floor stand
- Neutrik® powerCON® power input/output connections
- 3- and 5-pin DMX input/output connections
- LED display with password protection

## SPECIFICATIONS

- DMX Channels: 3, 4, 5, 6, 7, 12 or 17
- Data Connectors: 3- and 5-pin XLR
- Light Source: 14 LEDs (quad-color RGBW)  
15 W, (985 mA), 50,000 hours life expectancy
- Built-in Automated Programs: Yes
- Customizable Programs: Yes
- Recall Custom Programs: Yes
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Beam Angle: 6° to 30°
- Field Angle: 11° to 43°
- Zoom Angle: 11° to 43°
- Dimming Modes: 9
- Illuminance (11°): 8,000 lux @ 5 m
- Illuminance (43°): 695 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 7 units @ 120 V; 13 units @ 208 V; 14 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 205 W, 1.71 A @ 120 V, 60 Hz
- Power and Current: 208 W, 0.99 A @ 208 V, 60 Hz
- Power and Current: 212 W, 0.93 A @ 230 V, 50 Hz
- Weight: 17.8 lb (8.1 kg)
- Dimensions: 11.1 x 9.3 x 13.8 in (283 x 236 x 348 mm)
- Approvals: CE, MET