

COLORDash™ Par-Hex 7



FEATURES

- Intensely bright LED PAR wash fixture for a wide array of lighting applications
- 7 hex-color (RGBAW+UV) LED chips for ultimate color mixing
- Simple and complex DMX channel profiles for programming versatility
- Four distinct dimming modes for easy incandescent replacement
- Lightweight for easy installation
- Silent, flicker-free operation
- Neutrik® powerCON® power input/output connections

SPECIFICATIONS

- DMX Channels: 3, 6, 8, 12 or 13
- DMX Connectors: 3- and 5-pin XLR
- Light Source: 7 LEDs (hex-color RGBAW+UV)
10 W, (2.3 A), 50,000 hours life expectancy
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No
- Accessory Holder/
Gel Frame Size: 7.5 in (191 mm)
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Installed Optics: 25°
- Beam Angle: 21°
- Field Angle: 33°
- Dimming Modes: 4
- Illuminance (total): 512 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 27 units @ 120 V; 46 units @ 208 V; 52 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 60 W, 0.49 A @ 120 V, 60 Hz
- Power and Current: 61 W, 0.29 A @ 208 V, 60 Hz
- Power and Current: 60 W, 0.26 A @ 230 V, 50 Hz
- Weight: 7.2 lb (3.3 kg)
- Dimensions: 3.86 x 9.96 x 11.41 in (98 x 253 x 290 mm)
- Approvals: CE, MET