

<h1>Test Report</h1> <p>Issued by University of Salford (Acoustics Test Laboratory)  Date of Issue: 10<sup>th</sup> September 2024  Report Number: 06912/11</p>	
<p>Page 1 of 14</p>	
<p>APPROVED SIGNATORIES</p> <p>Claire Lomax [x]      Andy Moorhouse [ ]  Gary Phillips [ ]      Danny McCaul [ ]</p> 	
<p><b>acoustic test &amp; calibration laboratory</b></p> <p>The University of Salford, Salford, Greater Manchester, M5 4WT, UK  <a href="http://www.acoustics.salford.ac.uk">http://www.acoustics.salford.ac.uk</a>  t 0161 295 3030/0161 295 3319 f 0161 295 4456 e c.lomax1@salford.ac.uk</p>	

## Determination of airborne noise from an appliance

**Measurements described in this test report comply with:-**  
**BS EN ISO 3744:2010 ‘Acoustics. Determination of sound power levels and sound energy levels of noise sources using sound pressure. Engineering methods for an essentially free field over a reflecting plane’**

COMPANY NAME & ADDRESS:	Chauvet UK POD 1 EVO Park Nottingham NG16 6NT
FOR ATTENTION OF:	Ben Virgo
UNIT UNDER TEST:	Lighting Unit, ROGUE R3 ESPOT
DATE OF TEST:	28 <sup>th</sup> August 2024
TEST ENGINEER:	Sean Furlong
MEASUREMENT PURPOSE:	To determine airborne noise by measurements to the above standards.

*Results relate only to samples tested. Items tested are the samples supplied by the manufacturer, who was responsible for selecting at random from a standard production run.*

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 2 of 14

## 1.0 Description of Appliance Under Test

CATEGORY:	Lighting Unit
DESIGN CHARACTERISTICS:	Floor mounted
MANUFACTURER:	Chauvet
MODEL:	ROGUE R3 ESPOT
TEST REF NUMBERS:	06912/11_1 to 5
SERIAL NUMBER:	Not Stated
POWER:	Not Stated
POWER SOURCE:	UK Mains
SETTINGS: <i>*See Table 1.0 below for details of settings</i>	06912/11_1 “Ambient” 06912/11_2 “Max” 06912/11_3 “Auto” 06912/11_4 “Eco” 06912/11_5 “Full”

*\* Table 1.0 – Manufacturer’s description of the different settings of the sample that were used to create the Test Configuration for each measurement.*

Explanation of Settings Used for Each Test	
Setting Name	Test Configuration
Ambient	Unit is in idle state, switched on and no output or movements
Max	Unit is using all mechanical options, and the light output is on
Eco	All Effects Static, 100% Light output — ECO Fan mode
Auto	All Effects Static, 100% Light output — Auto Fan mode
Full	All Effects Static, 100% Light output — Full Fan mode

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 3 of 14

## 2.0 Test Conditions

2.1 The following conditions were measured over duration of the test:-

	Measured Average Value
<b>TEST REF NUMBER:</b>	<b>06912/11_1 to 5</b>
<b>SERIAL NO. / SAMPLE REF.</b>	<b>ROGUE R3 ESPOT</b>
Atmospheric Pressure	100.202
Ambient Temperature	23.2
Ambient Relative Humidity	56.4

2.2 The test was carried out in the hemi-anechoic chamber at the University of Salford.

2.3 The unit under test was mounted directly on the floor, in the centre of the hemi-anechoic chamber.

2.4 Unit operation was controlled by the client from outside the chamber, after initial configuration directly at the unit. Measurements were taken immediately after each setting of the unit was set and confirmed by the client.

2.5 For measurement of the sound pressure level of the Reference Sound Source (RSS), the RSS was placed directly on the floor of the hemi-anechoic chamber at the same location as the unit under test as defined in BS EN ISO 3744: 2010.

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 4 of 14



*Figure 1 – unit under test mounted in the hemi-anechoic chamber at the University of Salford.*

## 3 Acoustical Data

### 3.1 Measurement method

A direct measurement method was used as stated in BS EN ISO 3744: 2010.

### 3.2 Reference Sound Source

The Laboratory reference sound source (RSS) type B&K 4204, serial number 1460189 was used on mains supply.

### 3.3 Microphone Array

Ten laboratory free field, low noise microphones were used for the measurement, placed in fixed positions 1 to 10 on a hemispherical surface ( $d = 1.00$  m) with guidance from BS EN ISO 3744: 2010. The location of each measurement position is provided in Appendix 1 to this report.

### 3.4 Measured sound pressure levels of the unit

Each unit was run at the selected setting. Six measurements were made at each setting,

*This report is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to recognised national standards, and to the units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full except with the prior written approval of the issuing laboratory.*

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 5 of 14

Mean sound pressure levels were measured over 30 seconds to give the measured sound pressure levels,  $L_{pi}$  at each measurement position in each third octave band. The sound power level was then calculated.

The background noise corrections  $K_1$ , environmental correction calculated from RSS levels  $K_2$ , measured sound pressure levels,  $L_{pi}$  at each measurement point, corrected sound pressure levels,  $L_{pf}$ , and the sound power level,  $L_w$  of the source in each third octave frequency band are given in Appendix 2 of this report. The measured time averaged sound pressure level of the RSS,  $L'_{p(RSS)}$ , at each microphone position is reported in Appendix 3 to this report.

## 3.5 Calculated sound power levels

The calculated A-Weighted sound power level,  $L_{WA}$  in dBA for each setting are given in table 3.1.

Table 3.1 –A-weighted noise emissions for each setting, averaged over 30 seconds and over 10 microphone positions.

Test Number	06912/11_1	06912/11_2	06912/11_3	06912/11_4	06912/11_5
Setting	Ambient	Max	Auto	Eco	Full
A-weighted sound power level, $L_{WA}$ in dBA	17.2	48.2	46.4	44.3	53.3

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 6 of 14

## 3.6 Sound Pressure Level at 1 m from the source (not covered by BS EN 3744: 2010)

The A-weighted Sound Power Level can be used to calculate the A-weighted sound pressure level expected at different distances from the source in hemi-anechoic free field conditions\*.

The calculation of the sound pressure levels is based on the formulae in BS EN 3744: 2010 for a parallelepiped measurement surface (for a noise source measured, in this case, above a single reflective plane).

The calculations show that to estimate the average sound pressure level expected at a distance of 1 m from the surface of the unit, 13.1 dB should be subtracted from the sound power value. This would give A-weighted average sound pressure levels in table 3.2 for each unit setting at 1 m from the surface of the unit:-

Table 3.2 – Calculated A-weighted sound pressure level\* for each setting at 1 m from the unit surface

Test Number	06912/11_1	06912/11_2	06912/11_3	06912/11_4	06912/11_5
Setting	Ambient	Max	Auto	Eco	Full
A-weighted sound pressure level, $L_p$ in dBA	4.1	35.0	33.3	31.2	40.2

*\*This calculation represents an estimate of the levels that would be obtained in hemi-anechoic free field conditions and should not be assumed to be valid for any specific building environments where the characteristics of the room should be accounted for.*

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 7 of 14

## Appendix 1 – Locations of measurement positions

### Defining measurement surface & Co-ordinates

Measurement distance, d

1.00 m

	x, mm	y, mm	z, mm
Microphone Position 1	160	-960	220
Microphone Position 2	780	-600	200
Microphone Position 3	780	550	310
Microphone Position 4	160	900	410
Microphone Position 5	-830	320	450
Microphone Position 6	-830	-400	380
Microphone Position 7	-260	-650	710
Microphone Position 8	740	-70	670
Microphone Position 9	-260	500	830
Microphone Position 10	100	-100	990

Surface Area, m<sup>2</sup>

6.28 m<sup>2</sup>

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 8 of 14

## Appendix 2 – Measurements and calculations according to BS EN ISO 3744

The following tables include measurement details that provide in each third octave band, for each of the seven settings:-

- measured  $L_{pi}$ , averaged over 30 s, at each measurement position
- background noise corrections  $K_1$
- environmental correction  $K_2$ , calculated from RSS levels
- corrected sound pressure levels,  $L_{pf}$
- the sound power level,  $L_w$  of the source
- the A-weighted sound power level,  $L_{wA}$  of the source

! The levels at these frequencies are affected by background level and therefore levels quoted represent an upper limit for the sound pressure levels of the noise source.

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 9 of 14

MEASURED TIME AVERAGED SPL at 1 m, L'P - [06912/11_1 – "Ambient" Setting]											Mean L <sub>p</sub> over mic positions	$\Delta L_p$ [dB]	BG corr. K <sub>1</sub> , [dB]	Env corr. K <sub>2</sub> , [dB]	L <sub>p</sub> [dB]	Sound Power, L <sub>w</sub> [dB]	A- weighting corrections [dB]	Sound Power, L <sub>wA</sub> [dB]
Frequency [Hz]	Mic 1 [dB]	Mic 2 [dB]	Mic 3 [dB]	Mic 4 [dB]	Mic 5 [dB]	Mic 6 [dB]	Mic 7 [dB]	Mic 8 [dB]	Mic 9 [dB]	Mic 10 [dB]								
100	15.5	17.4	14.6	12.2	14.8	14.8	13.4	15.3	12.0	13.5	14.6	7.5	0.85	1.1	12.7	20.7	-19.1	1.6
125	7.7	9.0	3.7	5.0	5.4	5.6	2.4	1.0	4.7	-0.9	5.2	8.7	0.64	2.4	2.2	10.2	-16.1	-5.9
160	-0.3	1.1	0.5	-3.8	-4.1	-1.6	-4.0	-3.5	-3.2	-3.3	-1.8	3.5	1.30	0.7	-3.8	4.2	-13.4	-9.2
200	-3.6	-3.2	-4.7	-6.2	-5.5	-4.0	-5.4	-5.7	-7.0	-6.4	-5.0	1.0	1.30	0.5	-6.8	1.2	-10.9	-9.7
250	-6.0	-3.1	-6.0	-6.3	-4.3	-5.8	-5.5	-6.7	-5.9	-6.1	-5.4	1.2	1.30	0.6	-7.4	0.6	-8.6	-8.0
315	-9.0	-8.3	-8.4	-9.3	-10.0	-10.0	-9.4	-9.1	-9.8	-9.2	-9.2	0.9	1.30	0.3	-10.8	-2.8	-6.6	-9.4
400	-8.6	-6.8	-7.2	-8.4	-9.5	-8.7	-8.9	-8.6	-9.1	-8.8	-8.4	1.8	1.30	0.3	-10.0	-2.0	-4.8	-6.8
500	-8.7	-8.0	-9.3	-10.0	-9.9	-9.5	-8.6	-8.8	-9.4	-8.7	-9.1	0.8	1.30	0.2	-10.6	-2.6	-3.2	-5.8
630	-9.6	-8.2	-9.7	-10.4	-9.9	-9.7	-8.0	-8.9	-9.7	-8.6	-9.2	0.3	1.30	0.0	-10.5	-2.5	-1.9	-4.4
800	-9.0	-7.7	-8.8	-9.1	-9.3	-8.8	-7.5	-8.6	-9.0	-8.6	-8.6	0.5	1.30	-0.4	-9.5	-1.6	-0.8	-2.4
1000	-7.7	-7.0	-8.2	-8.1	-8.3	-7.9	-6.6	-7.8	-8.3	-7.9	-7.8	0.5	1.30	-0.9	-8.1	-0.1	0	-0.1
1250	-8.8	-6.3	-7.8	-8.2	-7.7	-7.8	-6.9	-7.2	-7.8	-7.4	-7.5	0.2	1.30	-1.2	-7.7	0.3	0.6	0.9
1600	-8.4	-5.6	-6.9	-7.4	-7.0	-7.0	-6.3	-6.5	-7.0	-6.8	-6.8	0.2	1.30	-0.6	-7.6	0.4	1	1.4
2000	-7.7	-5.1	-6.4	-6.7	-6.2	-6.4	-5.6	-5.7	-6.3	-6.2	-6.2	0.1	1.30	0.3	-7.8	0.2	1.2	1.4
2500	-7.0	-4.5	-5.8	-5.9	-5.5	-5.5	-4.9	-5.0	-5.6	-5.6	-5.5	0.1	1.30	-0.2	-6.6	1.4	1.3	2.7
3150	-6.5	-4.0	-5.4	-5.4	-5.0	-5.1	-4.5	-4.5	-5.1	-5.2	-5.0	0.1	1.30	0.5	-6.8	1.2	1.2	2.4
4000	-0.1	-2.9	-4.4	-4.8	-3.6	-4.5	-2.0	-2.5	-3.9	-4.3	-3.0	0.2	1.30	0.6	-4.9	3.0	1	4.0
5000	-4.5	-3.3	-4.4	-4.4	-4.0	-3.9	-3.6	-3.5	-4.0	-4.2	-4.0	0.0	1.30	-0.8	-4.4	3.6	0.5	4.1
6300	-4.9	-3.4	-4.1	-4.1	-3.9	-4.1	-3.6	-3.4	-3.8	-4.3	-3.9	0.1	1.30	-0.5	-4.7	3.2	-0.1	3.1
8000	-3.5	-2.2	-3.4	-3.4	-3.5	-3.7	-2.0	-2.6	-3.1	-3.6	-3.1	0.4	1.30	-0.3	-4.1	3.9	-1.1	2.8
10000	12.0	14.8	3.2	2.5	0.5	-2.1	16.5	9.4	-1.4	-1.2	10.2	12.7	0.24	0.5	9.5	17.4	-2.5	14.9
<b>A-WEIGHTED SOUND POWER LEVEL</b>																		<b>17.2</b>

*This report is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to recognised national standards, and to the units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full except with the prior written approval of the issuing laboratory.*

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 10 of 14

MEASURED TIME AVERAGED SPL at 1 m, L'P - [06912/11_2 – "Max" Setting]											Mean L <sub>p</sub> over mic positions	$\Delta L_p$ [dB]	BG corr. K <sub>1</sub> , [dB]	Env corr. K <sub>2</sub> , [dB]	L <sub>p</sub> [dB]	Sound Power, L <sub>w</sub> [dB]	A- weighting corrections [dB]	Sound Power, L <sub>wA</sub> [dB]
Frequency [Hz]	Mic 1 [dB]	Mic 2 [dB]	Mic 3 [dB]	Mic 4 [dB]	Mic 5 [dB]	Mic 6 [dB]	Mic 7 [dB]	Mic 8 [dB]	Mic 9 [dB]	Mic 10 [dB]								
100	20.6	20.7	19.5	19.3	19.9	20.0	19.6	18.9	18.0	16.8	19.5	12.4	0.26	1.1	18.1	26.1	-19.1	7.0
125	22.2	22.6	21.8	21.6	22.4	22.3	20.4	20.2	19.3	16.0	21.2	24.7	0.00	2.4	18.8	26.8	-16.1	10.7
160	27.2	27.9	28.5	27.6	27.1	26.9	26.2	25.2	24.3	23.1	26.7	31.9	0.00	0.7	25.9	33.9	-13.4	20.5
200	35.6	32.8	32.5	35.1	32.8	33.3	31.5	30.4	29.6	28.3	32.7	38.8	0.00	0.5	32.2	40.2	-10.9	29.3
250	32.1	32.3	31.5	31.0	31.5	32.2	28.2	30.5	28.0	29.7	30.9	37.5	0.00	0.6	30.3	38.3	-8.6	29.7
315	42.2	42.3	41.6	40.6	40.9	40.2	39.0	37.9	41.4	45.2	41.6	51.7	0.00	0.3	41.2	49.2	-6.6	42.6
400	30.9	30.7	31.1	30.5	29.8	30.9	28.6	27.9	28.3	29.6	30.0	40.1	0.00	0.3	29.6	37.6	-4.8	32.8
500	30.5	30.8	29.2	28.6	27.6	28.3	28.9	28.4	28.9	31.4	29.4	39.3	0.00	0.2	29.2	37.2	-3.2	34.0
630	30.1	31.0	27.9	27.0	26.8	27.1	29.7	29.9	30.3	32.8	29.7	39.1	0.00	0.0	29.7	37.7	-1.9	35.8
800	31.1	30.9	27.5	29.5	30.1	28.7	30.9	30.8	29.7	29.9	30.0	39.1	0.00	-0.4	30.4	38.4	-0.8	37.6
1000	30.9	30.5	29.3	32.1	32.9	31.4	31.8	30.7	30.9	29.9	31.2	39.4	0.00	-0.9	32.1	40.1	0	40.1
1250	27.6	26.4	28.8	30.5	30.2	30.4	29.4	28.8	29.0	28.4	29.1	36.9	0.00	-1.2	30.3	38.3	0.6	38.9
1600	27.4	26.7	29.2	29.1	29.0	29.6	28.2	28.4	28.4	27.5	28.4	35.5	0.00	-0.6	29.0	37.0	1	38.0
2000	24.9	25.4	26.6	25.6	26.3	26.3	26.2	26.4	25.9	24.9	25.9	32.2	0.00	0.3	25.6	33.6	1.2	34.8
2500	22.9	23.0	23.2	22.3	23.9	23.5	23.7	24.0	23.1	22.1	23.2	28.8	0.00	-0.2	23.5	31.4	1.3	32.7
3150	19.7	19.1	20.2	19.4	20.7	20.2	19.5	20.3	20.3	19.1	19.9	25.0	0.00	0.5	19.4	27.4	1.2	28.6
4000	18.6	18.8	18.7	18.1	19.3	19.5	18.3	19.3	18.9	16.9	18.7	21.9	0.00	0.6	18.1	26.1	1	27.1
5000	20.3	19.9	18.9	18.6	19.5	19.2	19.4	19.9	19.5	16.5	19.3	23.3	0.00	-0.8	20.1	28.1	0.5	28.6
6300	13.4	14.0	14.1	15.7	14.5	14.2	15.2	14.0	15.2	13.0	14.4	18.5	0.00	-0.5	14.9	22.9	-0.1	22.8
8000	13.1	11.6	12.7	16.1	13.1	13.4	14.4	12.5	14.3	12.2	13.5	17.0	0.00	-0.3	13.8	21.8	-1.1	20.7
10000	17.0	17.8	15.8	15.9	16.5	16.4	17.0	16.9	15.9	12.9	16.4	18.8	0.00	0.5	15.8	23.8	-2.5	21.3
<b>A-WEIGHTED SOUND POWER LEVEL</b>																		<b>48.2</b>

*This report is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to recognised national standards, and to the units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full except with the prior written approval of the issuing laboratory.*

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 11 of 14

MEASURED TIME AVERAGED SPL at 1 m, L'P - [06912/11_3 - "Auto" Setting]											Mean L <sub>p</sub> over mic positions	$\Delta L_p$ [dB]	BG corr. K <sub>1</sub> , [dB]	Env corr. K <sub>2</sub> , [dB]	L <sub>p</sub> [dB]	Sound Power, L <sub>w</sub> [dB]	A- weighting corrections [dB]	Sound Power, L <sub>wA</sub> [dB]
Frequency [Hz]	Mic 1 [dB]	Mic 2 [dB]	Mic 3 [dB]	Mic 4 [dB]	Mic 5 [dB]	Mic 6 [dB]	Mic 7 [dB]	Mic 8 [dB]	Mic 9 [dB]	Mic 10 [dB]								
100	22.3	23.6	22.7	21.8	22.4	22.2	21.8	22.2	20.3	24.5	22.5	15.4	0.00	1.1	21.4	29.4	-19.1	10.3
125	22.4	22.0	22.2	23.4	22.8	21.0	20.8	18.4	19.6	18.8	21.4	24.9	0.00	2.4	19.0	27.0	-16.1	10.9
160	24.7	23.0	25.1	25.5	23.0	22.0	23.7	19.0	19.1	20.5	23.1	28.3	0.00	0.7	22.4	30.4	-13.4	17.0
200	28.4	31.3	34.9	33.1	34.9	35.0	26.9	31.6	23.9	25.8	32.0	38.1	0.00	0.5	31.5	39.5	-10.9	28.6
250	28.7	30.4	31.3	31.1	31.0	30.2	23.2	28.8	25.8	23.8	29.2	35.8	0.00	0.6	28.6	36.6	-8.6	28.0
315	29.3	28.8	29.4	29.4	28.1	27.7	26.5	23.9	27.4	27.8	28.1	38.2	0.00	0.3	27.8	35.8	-6.6	29.2
400	28.4	27.2	29.5	29.3	26.6	28.5	27.5	25.0	27.9	26.5	27.8	38.0	0.00	0.3	27.5	35.5	-4.8	30.7
500	27.4	26.0	29.1	28.9	25.4	26.1	29.4	23.7	29.2	32.3	28.4	38.3	0.00	0.2	28.2	36.2	-3.2	33.0
630	27.9	25.4	29.7	28.0	24.6	27.0	29.2	25.3	28.7	35.5	29.4	38.9	0.00	0.0	29.4	37.4	-1.9	35.5
800	29.1	28.1	26.7	26.7	25.9	25.0	27.9	29.7	30.0	28.9	28.1	37.2	0.00	-0.4	28.4	36.4	-0.8	35.6
1000	29.9	29.1	27.1	34.0	31.6	25.7	28.5	32.7	32.8	30.9	30.9	39.1	0.00	-0.9	31.9	39.8	0	39.8
1250	28.1	26.3	25.7	32.9	30.8	24.8	28.1	28.9	30.7	28.5	29.1	36.9	0.00	-1.2	30.3	38.3	0.6	38.9
1600	27.5	26.2	27.5	34.0	29.7	26.9	29.1	26.5	28.5	29.9	29.3	36.3	0.00	-0.6	29.8	37.8	1	38.8
2000	23.3	22.4	26.0	29.1	24.7	24.7	26.8	23.7	25.5	24.2	25.5	31.7	0.00	0.3	25.1	33.1	1.2	34.3
2500	21.2	17.9	23.0	27.3	22.6	21.2	27.7	22.1	23.0	19.9	23.6	29.2	0.00	-0.2	23.9	31.8	1.3	33.1
3150	16.1	14.6	18.4	21.9	19.8	16.4	17.9	19.1	19.8	17.4	18.6	23.7	0.00	0.5	18.2	26.1	1.2	27.3
4000	14.9	13.7	17.2	20.2	16.0	15.9	16.1	15.4	17.3	14.0	16.5	19.7	0.00	0.6	15.9	23.9	1	24.9
5000	13.3	14.3	16.0	16.7	15.0	14.1	17.1	13.5	15.0	13.1	15.0	19.0	0.00	-0.8	15.9	23.8	0.5	24.3
6300	11.6	11.7	14.0	18.2	13.3	11.7	15.6	9.9	12.6	12.2	13.8	17.8	0.00	-0.5	14.3	22.2	-0.1	22.1
8000	11.9	8.9	9.8	16.4	9.1	9.4	14.6	7.9	11.8	8.8	11.8	15.2	0.00	-0.3	12.0	20.0	-1.1	18.9
10000	13.5	15.1	6.8	9.7	5.4	8.1	14.5	6.7	7.2	5.4	10.8	13.2	0.21	0.5	10.0	18.0	-2.5	15.5
<b>A-WEIGHTED SOUND POWER LEVEL</b>																		<b>46.4</b>

*This report is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to recognised national standards, and to the units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full except with the prior written approval of the issuing laboratory.*

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 12 of 14

MEASURED TIME AVERAGED SPL at 1 m, L'P - [06912/11_4 – "Eco" Setting]											Mean L <sub>p</sub> over mic positions	$\Delta L_p$ [dB]	BG corr. K <sub>1</sub> , [dB]	Env corr. K <sub>2</sub> , [dB]	L <sub>p</sub> [dB]	Sound Power, L <sub>w</sub> [dB]	A- weighting corrections [dB]	Sound Power, L <sub>wA</sub> [dB]
Frequency [Hz]	Mic 1 [dB]	Mic 2 [dB]	Mic 3 [dB]	Mic 4 [dB]	Mic 5 [dB]	Mic 6 [dB]	Mic 7 [dB]	Mic 8 [dB]	Mic 9 [dB]	Mic 10 [dB]								
100	18.3	18.8	19.0	18.8	19.4	18.7	18.3	17.8	17.0	20.5	18.8	11.6	0.31	1.1	17.4	25.3	-19.1	6.2
125	20.1	20.0	21.4	22.0	21.7	19.8	19.2	17.6	17.6	16.8	19.9	23.4	0.00	2.4	17.6	25.5	-16.1	9.4
160	23.3	21.8	24.3	24.4	22.3	21.0	22.6	18.3	17.5	19.5	22.0	27.3	0.00	0.7	21.3	29.3	-13.4	15.9
200	27.3	30.8	34.5	32.4	34.4	34.5	26.0	31.3	22.9	25.2	31.5	37.6	0.00	0.5	31.0	39.0	-10.9	28.1
250	26.3	28.5	29.2	28.8	28.9	28.0	21.1	27.3	24.7	24.0	27.3	33.9	0.00	0.6	26.6	34.6	-8.6	26.0
315	28.3	27.2	27.4	27.2	25.5	26.3	25.3	22.1	26.6	27.2	26.6	36.7	0.00	0.3	26.3	34.2	-6.6	27.6
400	26.4	25.4	25.7	25.7	23.2	24.5	24.3	21.2	25.8	24.2	24.9	35.0	0.00	0.3	24.5	32.5	-4.8	27.7
500	23.6	23.5	26.6	26.4	22.7	23.0	28.6	20.5	28.3	30.5	26.4	36.3	0.00	0.2	26.2	34.1	-3.2	30.9
630	25.7	23.6	26.8	23.7	20.9	23.2	25.7	22.2	25.2	31.4	25.9	35.4	0.00	0.0	25.9	33.9	-1.9	32.0
800	26.8	26.4	24.5	22.2	23.1	21.6	24.6	28.2	28.5	27.2	25.9	35.0	0.00	-0.4	26.3	34.2	-0.8	33.4
1000	26.8	27.5	24.8	32.3	30.4	23.7	24.0	32.1	31.6	28.1	29.2	37.4	0.00	-0.9	30.1	38.1	0	38.1
1250	24.7	23.9	23.9	31.5	30.0	22.3	22.7	27.7	29.8	25.1	27.3	35.1	0.00	-1.2	28.5	36.5	0.6	37.1
1600	22.4	22.0	25.9	33.1	28.7	25.2	24.9	23.9	27.0	26.7	27.3	34.3	0.00	-0.6	27.8	35.8	1	36.8
2000	19.8	19.3	24.9	28.0	23.1	21.7	22.1	22.0	23.6	20.5	23.3	29.6	0.00	0.3	23.0	31.0	1.2	32.2
2500	14.2	12.3	20.1	24.7	17.1	16.4	17.9	19.5	20.9	16.2	19.3	24.9	0.00	-0.2	19.5	27.5	1.3	28.8
3150	10.4	8.5	14.8	20.9	16.1	10.9	12.3	13.0	16.9	10.8	15.1	20.2	0.00	0.5	14.6	22.6	1.2	23.8
4000	11.2	8.9	14.9	19.3	13.4	12.3	10.9	9.6	15.3	9.0	13.8	17.0	0.00	0.6	13.2	21.2	1	22.2
5000	8.6	7.5	12.1	14.5	10.8	8.4	11.4	8.0	10.4	6.6	10.5	14.5	0.16	-0.8	11.2	19.2	0.5	19.7
6300	7.5	6.0	13.4	17.8	11.4	7.0	11.5	6.1	9.5	6.4	11.5	15.6	0.00	-0.5	12.0	20.0	-0.1	19.9
8000	8.5	6.0	8.4	14.6	6.6	5.9	11.4	5.4	8.7	4.6	9.2	12.6	0.24	-0.3	9.2	17.2	-1.1	16.1
10000	12.7	15.6	7.0	9.0	3.8	7.3	13.3	6.3	5.6	3.5	10.3	12.8	0.24	0.5	9.5	17.5	-2.5	15.0
<b>A-WEIGHTED SOUND POWER LEVEL</b>																		<b>44.3</b>

*This report is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to recognised national standards, and to the units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full except with the prior written approval of the issuing laboratory.*

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 13 of 14

MEASURED TIME AVERAGED SPL at 1 m, L'P - [06912/11_5 – "Full" Setting]											Mean L <sub>p</sub> over mic positions	$\Delta L_p$ [dB]	BG corr. K <sub>1</sub> , [dB]	Env corr. K <sub>2</sub> , [dB]	L <sub>p</sub> [dB]	Sound Power, L <sub>w</sub> [dB]	A- weighting corrections [dB]	Sound Power, L <sub>wA</sub> [dB]
Frequency [Hz]	Mic 1 [dB]	Mic 2 [dB]	Mic 3 [dB]	Mic 4 [dB]	Mic 5 [dB]	Mic 6 [dB]	Mic 7 [dB]	Mic 8 [dB]	Mic 9 [dB]	Mic 10 [dB]								
100	21.4	21.9	22.7	22.5	22.7	21.8	21.6	21.2	20.6	33.3	25.4	18.3	0.00	1.1	24.4	32.3	-19.1	13.2
125	26.0	24.9	25.3	26.7	25.5	24.0	24.4	21.7	23.0	27.1	25.1	28.6	0.00	2.4	22.7	30.7	-16.1	14.6
160	29.7	27.8	29.5	30.5	27.6	26.0	28.0	23.1	25.4	24.6	27.8	33.0	0.00	0.7	27.0	35.0	-13.4	21.6
200	32.7	30.9	32.9	35.8	31.9	31.0	28.5	27.5	27.2	27.1	31.5	37.5	0.00	0.5	31.0	38.9	-10.9	28.0
250	32.3	39.5	42.9	37.9	41.6	42.0	30.0	40.2	31.0	29.1	39.0	45.6	0.00	0.6	38.4	46.4	-8.6	37.8
315	34.2	33.7	35.5	34.4	33.8	35.0	32.5	31.6	31.7	32.9	33.7	43.8	0.00	0.3	33.4	41.4	-6.6	34.8
400	34.6	32.7	32.9	34.2	31.7	32.0	32.3	30.1	32.9	32.9	32.8	43.0	0.00	0.3	32.5	40.5	-4.8	35.7
500	35.6	33.5	35.4	34.7	31.2	33.0	34.0	30.5	34.5	37.1	34.3	44.2	0.00	0.2	34.1	42.1	-3.2	38.9
630	34.9	33.9	36.9	36.2	33.7	36.5	36.8	34.3	35.9	41.1	36.6	46.0	0.00	0.0	36.6	44.6	-1.9	42.7
800	36.0	33.8	32.8	34.2	32.2	31.3	34.8	35.1	35.9	35.1	34.4	43.5	0.00	-0.4	34.7	42.7	-0.8	41.9
1000	37.7	36.4	34.2	41.2	39.1	33.1	35.0	39.8	40.0	37.1	38.1	46.3	0.00	-0.9	39.0	47.0	0	47.0
1250	35.2	34.3	34.6	40.3	38.5	32.9	34.4	35.9	38.0	34.6	36.5	44.2	0.00	-1.2	37.7	45.6	0.6	46.2
1600	33.2	32.5	35.2	41.4	37.2	34.4	34.3	33.4	35.8	35.6	36.2	43.2	0.00	-0.6	36.7	44.7	1	45.7
2000	29.4	31.1	34.4	36.7	33.6	32.4	34.9	30.7	32.8	30.8	33.2	39.5	0.00	0.3	32.9	40.9	1.2	42.1
2500	25.9	25.2	30.7	32.7	28.4	27.6	29.3	29.3	30.2	26.7	29.2	34.8	0.00	-0.2	29.4	37.4	1.3	38.7
3150	23.8	22.2	26.5	30.4	27.4	23.4	24.5	25.4	27.4	23.3	26.1	31.3	0.00	0.5	25.7	33.7	1.2	34.9
4000	22.5	20.7	26.6	30.1	24.5	23.6	22.2	21.7	26.2	21.3	25.0	28.2	0.00	0.6	24.4	32.4	1	33.4
5000	19.7	19.9	24.8	25.8	22.9	20.4	23.7	20.3	22.8	19.5	22.6	26.6	0.00	-0.8	23.4	31.4	0.5	31.9
6300	17.4	17.1	20.8	24.3	19.2	17.2	20.3	16.4	19.3	17.1	19.6	23.7	0.00	-0.5	20.1	28.1	-0.1	28.0
8000	16.2	13.6	17.1	21.1	15.1	14.1	18.5	13.1	17.4	13.5	16.7	20.2	0.00	-0.3	17.0	25.0	-1.1	23.9
10000	14.3	16.2	12.5	15.3	10.6	11.1	16.7	9.4	13.2	10.2	13.6	16.1	0.00	0.5	13.1	21.1	-2.5	18.6
<b>A-WEIGHTED SOUND POWER LEVEL</b>																		<b>53.3</b>

*This report is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to recognised national standards, and to the units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full except with the prior written approval of the issuing laboratory.*

# Test Report

Issued by University of Salford (Acoustics Test Laboratory)

Date of Issue: 10<sup>th</sup> September 2024

Report Number: 06912/11

Page 14 of 14

## Appendix 3 – Measured time averaged sound pressure level of RSS, $L'_{P(RSS)}$ at each microphone position

Frequency	Mic 1	Mic 2	Mic 3	Mic 4	Mic 5	Mic 6	Mic 7	Mic 8	Mic 9	Mic 10	Average $L'_{P(RSS)}$ over microphone positions	Calculated Sound Power of RSS
[Hz]	[dB]	[dB]	[dB]									
100	68.8	70.8	70.1	68.3	70.8	70.2	67.6	68.9	66.9	60.7	69.0	76.9
125	70.8	71.9	70.7	69.9	71.4	70.5	67.9	69.3	68.0	61.9	69.9	77.8
160	70.5	70.9	70.8	69.6	68.4	68.8	68.4	67.7	65.9	62.6	68.9	76.9
200	71.1	69.9	70.1	70.4	68.7	69.4	67.4	67.4	64.8	62.6	68.8	76.8
250	70.2	70.6	70.0	69.2	69.3	69.8	66.3	67.8	65.1	63.9	68.7	76.7
315	70.4	70.7	70.2	69.1	68.8	69.2	66.7	66.4	65.8	65.8	68.7	76.7
400	71.0	71.1	70.4	69.2	68.5	69.6	65.1	65.9	64.2	64.6	68.7	76.7
500	71.4	71.9	70.8	69.0	68.1	69.5	64.9	64.6	64.9	66.0	68.9	76.9
630	71.7	72.1	70.5	68.1	66.9	69.0	66.4	65.6	67.9	69.6	69.3	77.3
800	72.6	72.5	69.8	66.0	65.5	67.5	70.2	69.1	71.7	72.6	70.4	78.4
1000	72.3	73.0	67.9	65.0	65.6	65.6	73.2	72.9	72.7	70.9	70.9	78.9
1250	70.0	72.6	65.7	71.3	72.9	69.9	73.4	74.3	71.4	75.1	72.3	80.3
1600	66.0	68.1	72.0	75.4	75.9	74.8	71.6	71.0	74.2	73.4	73.1	81.1
2000	68.7	67.6	74.9	75.5	74.6	75.6	74.0	73.6	73.4	71.7	73.6	81.6
2500	71.8	69.1	73.8	71.6	70.6	72.5	71.0	71.9	70.1	68.3	71.3	79.3
3150	75.2	73.2	72.5	71.8	72.4	70.7	70.1	71.1	69.5	66.2	71.8	79.8
4000	73.6	73.7	70.7	72.9	72.3	72.7	70.5	71.2	69.0	66.3	71.8	79.7
5000	68.9	70.4	71.4	70.7	70.6	70.5	69.2	69.9	68.1	64.2	69.7	77.7
6300	69.6	69.4	70.3	69.7	69.6	69.8	67.8	68.8	67.1	62.6	68.9	76.9
8000	67.6	67.8	69.2	68.3	68.0	67.8	66.5	67.6	66.4	61.1	67.4	75.4
10000	66.0	66.5	67.5	66.9	67.1	67.1	65.0	66.4	65.1	59.7	66.1	74.1

*This report is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to recognised national standards, and to the units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full except with the prior written approval of the issuing laboratory.*