

WELL POD 2X6

FEATURES

- A fully realized kit of (6) Battery operated black IP65 rated par style fixture with (19) RGB Warm White LEDs and a beam angle of 16.5 degrees, lens and diffusion filter packs, white covers, removable yokes, omega brackets, and an RF remote all packaged inside of a (6) fixture charging case.
- Battery run time selections of 3, 5, 8, and 12 hours of operation at full output
- Built in battery charger allows fixture to operate while charging
- Built in IP65 5 pin DMX in/out allows for wired data
- Built in Seetronic IP65 PowerKon input/output
- Control over DMX, CRM, RDM, or RF
- Easy connection to WELL COM and WELL COM V2 boxes for App control
- USB-C port for convenient software updates
- Removable split yoke for both hanging and floor standing
- Pressure equalizing M12 Gore valve
- Adjustable front foot for adjusting fixture angle when yoke is removed
- Kensington lock position
- Built in safety cable attachment point
- Easy to read OLED display
- Built in theft alarm (audio and visual notification)
- Built in PWM Adjustment
- Included filter pack for beam shaping options
- Included egg crate for glare reduction
- Included metal white cover for elegant events
- Included RF remote
- Included 6 pack charging case



SPECIFICATIONS

OPTICAL

- Light Source: 19 LEDs (RGBWW), 13.4W, (960mA) 50,000 hours life
- Color Temperature (at full): 8774 K
- Beam Angle: 16.5°
- Field Angle: 34.1°
- Illuminance (total): 987 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 1 to 30 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4

- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No

CONSTRUCTION / PHYSICAL

- Dimensions: 9.76 x 7 x 10.86 in (248 x 178 x 276)
- Dimensions (w/o bracket): 9.76 x 7 x 7 in (248 x 178 x 178 mm)
- Dimensions case: 36.7 x 25.2 x 19.3" (933 x 641 x 492mm)
- Weight: 11.2 lbs (5.1 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic TRUE1 IP65
- Power Input: Seetronic TRUE1 IP65
- Power Output: Seetronic TRUE1 IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX512, RDM, W-DMX, 433RF
- DMX Channels: 4, 8, or 13
- Modes/Personalities: 3 personalities (4, 8, 13)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 79 W, 0.74 A @ 120 V, 60 Hz
- Power and Current: 56 W, 0.43 A @ 208 V, 60 Hz
- Power and Current: 56 W, 0.39 A @ 230 V, 50 Hz
- 6 units in charging case
 - Power and Current: 421 W, 5.81 A @ 120 V, 60 Hz
 - Power and Current: 409 W, 3.16 A @ 208 V, 60 Hz
 - Power and Current: 407 W, 2.82 A @ 230 V, 50 Hz

BATTERY

- Battery type: Lithium Ion
- Rechargeable: Yes
- Battery Charge Time: 2.53 hours
- Battery Life: 3hr, 5hr, 8hr, 12hr
- Battery Power: 25.9V, 6.6 Ah

CERTIFICATIONS / QUALIFICATIONS

- CE, UKCA, FCC, ROHS
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): 14 °F to 113 °F (-10 °C to 45 °C)

WHAT'S INCLUDED

- (6) WELL POD 2
- (1) Charging case
- (6) White sleeves
- (6) magnetic filter frames
- (6) 105mm omega brackets
- (6) filter packs (15 degree, 60x30 degree, 60x10 degree)
- (6) detachable split yokes
- (1) RF controller
- (1) QRG

OPTIONAL ACCESSORIES

- Clamps
- IP 65 PowerKon cables
- DMX Cables