

WELL POD 3x4

FEATURES

- A fully realized kit of (4) Battery operated black IP65 rated par style fixture with (19) RGB Warm White LEDs and a beam angle of 12.7 degrees
- Battery run time selections of 5, 8, 12, and 18 hours of operation at full output
- Built in battery charger allows fixture to operate while charging
- Built in IP65 5 pin DMX in/out allows for wired data
- Built in Seetronic IP65 PowerKon input/output
- Control over DMX, CRMX, RDM, or RF
- Easy connection to WELL COM and WELL COM 2 boxes for App control
- USB-C port for convenient software updates
- Removable split yoke for both hanging and floor standing
- Pressure equalizing M6 Gore valve
- Built in safety cable attachment point
- Easy to read OLED display
- Built in theft alarm (audio and visual notification)
- Built in PWM Adjustment
- Included RF remote
- Included 4 pack charging case



SPECIFICATIONS

OPTICAL

- Light Source: 19 LEDs (RGBWW), 13.4W, (960mA) 50,000 hours life
- Color Temperature (at full): 8774 K
- Beam Angle: 12.7°
- Field Angle: 25.4°
- Lumens: 3411 lm (AC power)
- Illuminance: 1480 lux @ 5 m (AC power) Lumens:
- Lumens: 1937 lm (OFF battery setting)
- Illuminance: 824 lux @ 5 m (OFF battery setting)
- Lumens: 2104 lm (5 hour battery setting)
- Illuminance: 913 lux @ 5 m (5 hour battery setting)
- Lumens: 1345 lm (8 hour battery setting)
- Illuminance: 579 lux @ 5 m (8 hour battery setting)
- Lumens: 806 lm (12 hour battery setting)
- Illuminance: 351 lux @ 5 m (12 hour battery setting)
- Lumens: 531 lm (18 hour battery setting)
- Illuminance: 229 lux @ 5 m (18 hour battery setting)
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 1 to 30 Hz
- Standalone Color Mixing: Yes

- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No

CONSTRUCTION / PHYSICAL

- Dimensions: 9.76 x 7 x 10.86 in (248 x 178 x 276)
- Dimensions (w/o bracket): 9.76 x 7 x 7 in (248 x 178 x 178 mm)
- Dimensions case: 36.7 x 25.2 x 19.3" (933 x 641 x 492mm)
- Weight: 11.2 lbs (5.1 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic Powerkon IP65
- Power Input (fixture and charging case): Seetronic Powerkon IP65
- Power Output(fixture and charging case): Seetronic Powerkon IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)
- Software Connection: USBc

CONTROL

- Control Protocol: RDM, CRMX, NFC, RF
- DMX Channels: 4, 8, or 13
- Modes/Personalities: 3 personalities (4Ch, 8Ch, 13Ch)
- Wireless WDMX "G" Compatibility: G4S
- Wireless Lumen Radio Compatibility: CRMX

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 79 W, 0.74 A @ 120 V, 60 Hz
- Power and Current: 56 W, 0.43 A @ 208 V, 60 Hz
- Power and Current: 56 W, 0.39 A @ 230 V, 50 Hz
- **6 units in charging case**
- Power and Current: 421 W, 5.81 A @ 120 V, 60 Hz
- Power and Current: 409 W, 3.16 A @ 208 V, 60 Hz
- Power and Current: 407 W, 2.82 A @ 230 V, 50 Hz

BATTERY

- Battery type: Lithium Ion
- Rechargeable: Yes
- Battery Charge Time: 2.53 hours
- Battery Life: 3hr, 5hr, 8hr, 12hr
- Battery Power: 25.9V, 6.6 Ah

CERTIFICATIONS / QUALIFICATIONS

- CE, UKCA, FCC, ROHS
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): 14 °F to 113 °F (-10 °C to 45 °C)

WHAT'S INCLUDED

- (6) WELL POD 3
- (1) Charging case
- (6) omega brackets
- (6) detachable split yokes
- (1) RF controller

- (1) QRG

OPTIONAL ACCESSORIES

- Clamps
- Lens pack (15 degree, 60x10 degree)
- Single charger
- White metal cover
- IR remote
- PowerKon Extension cables
- 5 pin DMX Cables
- WELL COM 2
- WELL COM 2 App
- WELL COM 2 App
- W-DMX Micro T-1 TRX G6